

RIG 112

15TE BREAKBACK TRACKED ENGINE

Our 15Te tracked engine, Rig 112, is designed to be used in the laying and retrieval of subsea cables used within such industries as the power industry and telecommunication industry. This tracked engine has an assisted render function which allows the set tension to be held constant by controlling the speed of the tracks automatically. The break back function allows the top track to pivot out of the firing line to pass a quadrant through. It is powered by an integrated hydraulic power pack and controlled with a remote ergonomically designed control desk. It is of robust design and is suitable to be operated in the most hazardous environments the industry has to offer.



KEY FEATURES

- maximum dynamic pull tension 15Te*
- maximum speed in excess of 45m/min
- break back function pivots top track out of firing line to pass quadrant
- suitable for cable sizes between 50mm and 400mm
- self-contained control desk
- full colour touchscreen HMI
- simple deck installation with removable feet
- in an emergency, or power loss situations, the tracks will stay in their position and can hold the product for over 1 hour.

* Please note that the maximum tension achievable will depend upon the type and size of cable due to friction factor limitations, and the general lay conditions.

Image for Illustration Purposes only



SPECIFICATIONS

Height	3,350mm
Width	2,200mm
Length	5,855mm
Track contact length	3,120mm
Track squeeze force	0 - 60Te variable
Weight	15Te
Control modes	manual/auto/assisted render
Power requirements	415V/125A
Length of data cable between TE and control desk	15m (if required) this can be lengthened
Tension readout accuracy	Usually within 5% (on site calibration required)
Bridge readout capability	RS 232/ 485 on request

Orientation: Port / Left Hand

General Arrangement Drawing: 23552-M-1000

DS-R112-IHC-001



**THE TECHNOLOGY
INNOVATOR.**

ROYAL IHC LTD.
Neptune Energy Park
Fisher Street, Walker
Newcastle upon Tyne, NE6 4LY

T 0191 263 7272
www.royalihc.com